

Stainless Steel One Hole Strap

Features and Benefits

- Manufactured in 316 stainless steel for superior corrosion resistance, exceptional strength, and outstanding performance in harsh environments.
- Hygienic polished surface improves cleanability, resists microbial buildup, and delivers a consistent, professional appearance.
- Permanent fiber laser identification eliminates contamination risks and maintains traceability without surface marring.
- Heavy-gauge stainless steel construction maintains shape and support under mechanical stress.

Applications

- RMC's type 316 stainless steel One Hole Straps are built for heavy-duty performance, providing secure support and mounting of stainless steel Rigid Conduit to multiple structural members and flat surfaces in corrosive or demanding environments.

Material

- Body: Type 316 Stainless Steel

Certifications

- UL/cUL 2239 Listed
- UL File # E516500
- RoHS compliant
- REACH compliant



Part Number	Trade Size	A	B	C	T	Bolt Hole Size	WT/PC (lbs.)
SR61H05	1/2"	0.835"	0.625"	0.840"	0.071"	0.250"	0.04
SR61H07	3/4"	0.992"	0.744"	1.050"	0.079"	0.375"	0.05
SR61H10	1"	1.465"	0.866"	1.314"	0.079"	0.375"	0.07
SR61H12	1-1/4"	1.660"	0.866"	1.660"	0.079"	0.438"	0.11
SR61H15	1-1/2"	1.886"	1.000"	1.900"	0.098"	0.438"	0.15
SR61H20	2"	2.303"	1.126"	2.376"	0.110"	0.562"	0.23
SR61H25	2-1/2"	2.780"	1.236"	2.876"	0.150"	0.562"	0.44
SR61H30	3"	3.425"	1.236"	3.500"	0.150"	0.562"	0.50
SR61H40	4"	4.571"	1.236"	4.500"	0.177"	0.562"	0.71